



Colour paint

Technical data sheet

750ml / Item no.104703401 / EAN 4007955104735 (Wild grapevine)
750ml / Item no.105003401 / EAN 4007955105008 (A Natural Night)
750ml / Item no.105103401 / EAN 4007955105138 (Bright Horizon)
750ml / Item no.104903401 / EAN 4007955104933 (Fresh fern)
750ml / Item no.104503401 / EAN 4007955104537 (Warm desert sand)



A silicate-based mineral-coloured paint for decorating walls and ceilings. Suitable for tinting almost all proMineral products* or for use as a solid colour. For an even wider range of colours, the five shades can also be mixed together.

- exceptionally vivid colours
- good mixing properties
- highly breathable and vapour-permeable
- free from preservatives and plasticisers
- Wet abrasion resistance: Class R 2 in accordance with DIN EN 13300
- Gloss level: matt (G3 in accordance with DIN EN 13300)

Area of application

Mineral silicate coloured paint for walls and ceilings. For tinting or for use as a solid colour. Shades can be mixed together.

Preparation

The substrate must be dry, clean and sound. Remove any old paint that is not firmly adhering, distemper and loose plaster. Pre-treat highly absorbent, sandy and chalky surfaces with proMineral primer.

Processing

Depending on the desired colour shade, the coloured paint can be used as a full-tone paint, tinted or mixed with another colour shade. Stir the paint thoroughly before use and apply with a brush, roller or a suitable spray gun. If using the same colour shade, mix different batches together before application. Colour variations may occur depending on the paint being tinted and the nature of the substrate. See the lid for batch number and colour shade. Do not apply when the substrate or room temperature is below +5 °C. Clean tools with water immediately after use.

Drying time:

Under normal conditions (20 °C, 65% relative humidity, moderately absorbent substrate), the drying time is approx. 6–12 hours. Under unfavourable conditions (e.g. low temperature or high humidity), the drying time may be extended.

Consumption

750 ml is sufficient for approx. 4 m² with a single coat – depending on the condition of the substrate. Determine the exact amount required by carrying out a test application on the surface.

Storage

Store containers tightly sealed in a cool place, but away from frost. Do not allow the product to enter the sewerage system, soil or watercourses. Only send completely empty containers for recycling. Dried-out residues can be disposed of with household waste or as construction site waste. When unopened and stored correctly, the product has a shelf life of up to 60 months from the date of manufacture.

Notes

* The coloured paint is not suitable for tinting proMineral lime-mineral paint, proMineral lime roller plaster or proMineral primer.

Note:

All details and data presented in this information sheet are based on our practical experience and laboratory investigations, and reflect the current state of the art. They can, however, only serve as general guidance and shall provide no guarantee of specific properties or performance. Given that the conditions for storage, transportation and application of products are beyond our control, no legal liability may be construed from the information presented here. It shall be the responsibility of the user to check the product's suitability for the envisaged purpose under the specific site or project conditions.

Keep out of reach of children. Due to the high pH value, avoid contact with the eyes and skin. It is recommended that you wear gloves and safety goggles (not glass). In case of skin contact, rinse thoroughly with plenty of water. In case of eye contact, rinse immediately with plenty of water and seek medical advice if necessary.

Please refer to the safety data sheet for safety-related information. Up-to-date safety data sheets are available on our website www.pro-mineral.com.

EU VOC limit value for this product (Cat.: A/a, Wb) = 30 g/l (2010). Maximum VOC content of this product: 1 g/l.

Note:

All details and data presented in this information sheet are based on our practical experience and laboratory investigations, and reflect the current state of the art. They can, however, only serve as general guidance and shall provide no guarantee of specific properties or performance. Given that the conditions for storage, transportation and application of products are beyond our control, no legal liability may be construed from the information presented here. It shall be the responsibility of the user to check the product's suitability for the envisaged purpose under the specific site or project conditions.