Primer

Technical data sheet

5l / Item number 066302401 / EAN 4007955663126



Mineral-based primer. The proMineral primer creates a stable and uniformly absorbent substrate that is ideal for subsequent coats of proMineral products. Suitable for use on mineral substrates (such as gypsum, lime and cement render, masonry and concrete), as well as plasterboard, gypsum fibreboard and similar substrates in interior applications. Dries to a transparent finish.

- the ideal base for lime, clay and silicate products
- strengthens sandy and chalky substrates
- regulates absorbency
- ready to use
- vapour-permeable
- free from preservatives and plasticisers
- free from ingredients of animal origin

Area of application

Mineral-based primer for interior use. Creates a stable, uniformly absorbent substrate for proMineral coatings and dries to a clear finish.

Preparation

The surface must be dry, clean and free of grease. Remove any old paint that is not firmly adhering and any loose plaster. Cover surfaces that do not require priming with plastic sheeting before application.

Processing

Stir the primer thoroughly before use and apply it undiluted to the substrate using a paintbrush or brush. Avoid splashing onto glass, aluminium, ceramics, marble and similar materials. Remove any accidental splashes immediately with water. Do not carry out any further work until the primer has dried completely. Do not apply when the substrate and ambient temperature are below +5 °C. Clean tools with water immediately after use. Do not mix with other products.

Drying time:
Under normal conditions (20 °C, 65% relative humidity, moderately absorbent substrate), the drying time is approx. 4 hours. Under unfavourable conditions (e.g. low temperature or high humidity), the drying time may be extended.

Consumption

1 litre is sufficient for approx. 6–8 m² with a single coat – depending on the condition of the substrate. Determine the exact amount required by carrying out a test application on the surface.

Storage

Store containers tightly sealed in a cool place, but away from frost. Do not allow the product to enter the sewer system, watercourses or the ground. Only send completely empty containers for recycling. Dried-out residues can be disposed of with household waste or as construction site waste.

decotric GmbH ■ Im Schedetal 1 ■ 34346 Hann. Münden ■ Telephone +49 (0)55 41-70 03 02 ■ Email info@decotric.de ■ www.pro-mineral.com

Note:
All details and data presented in this information sheet are based on our practical experience and laboratory investigations, and reflect the current state of the art. They can, however, only serve as general guidance and shall provide no guarantee of specific properties or performance. Given that the conditions for storage, transportation and application of products are beyond our control, no legal liability may be construed from the information presented here. It shall be the responsibility of the user to check the product's suitability for the envisaged purpose under the specific site or project conditions.

Notes

Keep out of the reach of children. Due to the high pH value, avoid contact with the eyes and skin. It is recommended that you wear gloves and safety goggles (not glass). In case of skin contact, rinse thoroughly with plenty of water. In case of eye contact, rinse immediately with plenty of water and seek medical advice if necessary.

Please refer to the safety data sheet for safety-related information. Up-to-date safety data sheets are available on our website www.pro-mineral.com.

EU VOC limit value for this product (Cat.: A/h, Wb) = 30 g/l (2010). Maximum VOC content of this product: 1 g/l.

decotric GmbH ■ Im Schedetal 1 ■ 34346 Hann. Münden ■ Telephone +49 (0)55 41-70 03 02 ■ Email info@decotric.de ■ www.pro-mineral.com

Note:
All details and data presented in this information sheet are based on our practical experience and laboratory investigations, and reflect the current state of the art. They can, however, only serve as general guidance and shall provide no guarantee of specific properties or performance. Given that the conditions for storage, transportation and application of products are beyond our control, no legal liability may be construed from the information presented here. It shall be the responsibility of the user to check the product's suitability for the envisaged purpose under the specific site or project conditions.