



Ready-mixed mineral filler

Technical data sheet

15kg / Item no.121405401 / EAN 4007955121459



Ready-to-use, white, silicate-based filler for interior walls and ceilings. Suitable for use on all mineral substrates (e.g. gypsum, lime and cement plasters, calcium silicate boards, concrete, etc.) as well as on firmly adhering existing coatings of mineral or matt, absorbent emulsion paints. This ready-to-use mineral-based filler is easy to apply and smooth, and can be sanded very easily once thoroughly dry. The preservative-free filler is vapour-permeable and moisture-regulating, thereby helping to maintain a comfortable indoor climate.

- Silicate-based filler
- for mineral substrates and painted surfaces
- the perfect base for all proMineral products
- very easy to sand
- vapour-permeable
- moisture-regulating
- free from preservatives and plasticisers
- free from ingredients of animal origin

Area of application

Ready-to-use silicate-based filler for interior walls and ceilings. Easy to apply and excellent for sanding; it is breathable and helps regulate humidity.

Preparation

The substrate must be solid, dry, stable, clean and free from release agents. Remove old wallpaper, poorly adhering paint and loose plaster. Pre-treat highly absorbent, sandy and chalky substrates with proMineral primer.

Processing

Stir thoroughly before use. Apply with a trowel or smoothing trowel and smooth the surface. When applied over the entire surface, the maximum layer thickness is 5 mm. Do not apply when the substrate or room temperature is below +5 °C. Clean tools with water immediately after use.

Consumption

approx. 1.4 kg/m² at an application thickness of 0.8 mm.

Storage

Store containers tightly sealed in a cool place, but away from frost. Do not allow the product to enter the sewer system, watercourses or the ground. Only send completely empty containers for recycling. Dried-out residues can be disposed of with household waste or as construction site waste.

Notes

Keep out of the reach of children. Due to the high pH value, avoid contact with the eyes and skin. It is recommended that you wear gloves and safety goggles (not glass). In the event of skin contact, rinse thoroughly with plenty of water. In the event of eye contact, rinse immediately with plenty of water and seek medical advice if necessary. Do not inhale grinding dust.

Note:

All details and data presented in this information sheet are based on our practical experience and laboratory investigations, and reflect the current state of the art. They can, however, only serve as general guidance and shall provide no guarantee of specific properties or performance. Given that the conditions for storage, transportation and application of products are beyond our control, no legal liability may be construed from the information presented here. It shall be the responsibility of the user to check the product's suitability for the envisaged purpose under the specific site or project conditions.

Please refer to the safety data sheet for safety-related information. Up-to-date safety data sheets are available on our website at www.pro-mineral.com.

Note:

All details and data presented in this information sheet are based on our practical experience and laboratory investigations, and reflect the current state of the art. They can, however, only serve as general guidance and shall provide no guarantee of specific properties or performance. Given that the conditions for storage, transportation and application of products are beyond our control, no legal liability may be construed from the information presented here. It shall be the responsibility of the user to check the product's suitability for the envisaged purpose under the specific site or project conditions.