White interior

Technical data sheet

5l / Item number 066502401 / EAN 4007955665120
10l / Item number 066503401 / EAN 4007955665137



For interior wall and ceiling painting. For mineral substrates (such as lime and cement plaster, masonry and concrete), as well as woodchip wallpaper, mineral paint fleece, plasterboard and gypsum fibreboard, and similar substrates. Thanks to its microcrystalline structure, the paint has a high water vapour permeability, thereby helping to maintain a comfortable indoor climate.

- for white, cloth-matt finishes
- free from preservatives and plasticisers
- free from ingredients of animal origin
- Contrast ratio: H_{10} Class 2 with a coverage of 6 m²/l
- Resistance to wet abrasion: Class R 3 in accordance with DIN EN 13300
- Gloss level: G4 matt
- Max. grain size: S1 (fine)

Area of application

A breathable interior paint for walls and ceilings. Ideal for use on mineral-based surfaces, woodchip wallpaper and plasterboard.

Preparation

The substrate must be dry, clean and sound. Remove any old paint that is not firmly adhering, distemper and loose plaster. Pre-treat highly absorbent, sandy and chalky surfaces with proMineral primer.

Processing

Stir the interior white paint thoroughly before use and apply with a brush, roller or a suitable spray gun. Apply two coats if necessary. The first coat may be thinned with a maximum of 5 per cent water. Apply the top coat undiluted once the first coat has dried thoroughly. Do not apply when the substrate or room temperature is below +5 °C. Clean tools with water immediately after use.

Tinting:
For coloured finishes, the interior white paint can be tinted with a maximum of 3 per cent universal tinting concentrates (LW-Oxyd types only) or with proMineral coloured paints.

Drying time:
Under normal conditions (20 °C, 65 % relative humidity, moderately absorbent substrate), the drying time is approx. 6–12 hours. Under unfavourable conditions (e.g. low temperature or high humidity), the drying time may be extended.

Consumption

1 litre is sufficient for approx. 6–8 m² with a single coat – depending on the condition of the substrate. Determine the exact amount required by carrying out a test application on the surface.

Storage

Store the container tightly sealed in a cool place, but away from frost.

decotric GmbH ■ Im Schedetal 1 ■ 34346 Hann. Münden ■ Telephone +49 (0)55 41-70 03 02 ■ Email info@decotric.de ■ www.pro-mineral.com

Note:
All details and data presented in this information sheet are based on our practical experience and laboratory investigations, and reflect the current state of the art. They can, however, only serve as general guidance and shall provide no guarantee of specific properties or performance. Given that the conditions for storage, transportation and application of products are beyond our control, no legal liability may be construed from the information presented here. It shall be the responsibility of the user to check the product's suitability for the envisaged purpose under the specific site or project conditions.

Notes

Keep out of the reach of children. Due to the high pH value, avoid contact with the eyes and skin. It is recommended that you wear gloves and safety goggles (not glass). In case of skin contact, rinse thoroughly with plenty of water. In case of eye contact, rinse immediately with plenty of water and seek medical advice if necessary.

Please refer to the safety data sheet for safety-related information. Up-to-date safety data sheets are available on our website www.pro-mineral.com.

EU VOC limit value for this product (Cat.: A/a, Wb) = 30 g/l (2010). Maximum VOC content of this product: 0.5 g/l.

decotric GmbH ■ Im Schedetal 1 ■ 34346 Hann. Münden ■ Telephone +49 (0)55 41-70 03 02 ■ Email info@decotric.de ■ www.pro-mineral.com

Note:
All details and data presented in this information sheet are based on our practical experience and laboratory investigations, and reflect the current state of the art. They can, however, only serve as general guidance and shall provide no guarantee of specific properties or performance. Given that the conditions for storage, transportation and application of products are beyond our control, no legal liability may be construed from the information presented here. It shall be the responsibility of the user to check the product's suitability for the envisaged purpose under the specific site or project conditions.